

MasterMover®

MT5/400+ SS

Battery powered electric tug



MT5/400+ SS



Overview

The Stainless Steel range of electric tugs delivers the same level of performance as our mild steel ranges, but with the added benefit of seamlessly integrating into sterile environments.

Whether it's a biopharmaceutical cleanroom suite or a food manufacturing facility, our stainless steel electric tugs remove manual handling and drive operational efficiency without compromising the cleanliness of your facility.

Constructed from high-grade 316 stainless steel and with IP ratings of up to IP55 available, stainless steel electric tugs are ideally suited to the stringent requirements of sterile environments.

The Stainless Steel range of electric tow tugs facilitate the controlled movement of loads in tight spaces, with an array of coupling options available that put load security and safety at the forefront.

Key Features

Safety

- Audible horn, flashing safety light, emergency stop button and anti-crush button
- Speed control with an optional two-speed selector switch for maximum control
- Complete load security with automatic braking

Power

- Optimised motor output to optimise speed and power
- Maintenance-free, interchangeable battery options
- Powerful, effective, traction generation for smooth performance

Performance




- Powerful weight-moving capabilities suited to every application
- Maximum traction even on wet floors
- Compact and manoeuvrable to deliver precise movements in even the tightest of spaces

Connection

- Secure coupling systems to deliver the controlled movement of loads
- A range of coupling options available to connect to a variety of loads
- Custom couplings available



Dimensions




Slope Performance

The force required to move a load is based on load weight, slope angle and floor condition. Movement on a slope increases the force required to safely start, stop and move the load.

If your application involves moving a load up or down a slope, speak to our team who will be happy to advise on which machine will meet your requirements.








* Variables that affect rolling resistance include the quality of floor/terrain and the type/condition/quality of castor wheels.









In Application: MasterTug Stainless Steel



Standard Safety Features

<p>Emergency Stop Button</p> 	<p>Anti-Crush Button</p> 	<p>Warning Horn</p> 
<p>Automatic Parking Brake</p> 	<p>Automatic Cut Off</p> 	<p>Battery Discharge Indicator</p> 
<p>Key Switch</p> 		


Machine Options

<p>Additional Battery Z71-00300</p>	<p>Flashing Light & Motion Beeper Z62-00500</p>	<p>Two Speed Selector Switch Z62-00501</p>
 A 3D rendering of a rectangular metal battery box with a black battery pack inside, featuring red and blue terminals.	 A vertical black cylindrical component with a yellow flashing light at the top and a silver mounting post.	 A close-up of a black control panel with a yellow rectangular selector switch.
<p>Drive Wheel - 316 Stainless Steel Z62-00502</p>	<p>CombiLock Z62-00502</p>	<p>Quick Release Coupling Pins Z62-00503</p>
 A blue, treaded drive wheel with a stainless steel inner rim.	 A close-up of a silver metal locking mechanism with a handle and a latch.	 A close-up of a black metal component with three silver quick-release pins.

Couplings

CombiCoupling

Z71-00600 male | Z71-00700 female



BoxCoupling

Z71-00601 male | Z71-00701 female



Custom Engineering

We understand that every application is different. Whether it's a custom coupling to connect to your load, modifying our electric tugs to work in a challenging environment, or designing an entirely new solution for your application, our Customer Engineering team are here to help.

For more information on our custom engineering capabilities, please visit: mastermover.com/custom-solutions
If you'd like to discuss your requirements, speak to your sales representative or email: sales@mastermover.com

Technical Specification

Machine	
Product code	Z71-00102
Maximum load (on castors on rails)	4,000 kg 16,000 kg
Maximum force (push pull)	3,924 N 3,924 N
Machine weight	210 kg
Battery weight (standard)	73 kg
Combined machine & battery weight (standard)	283 kg
Drive type	Electric
Braking	Regenerative
Parking brake	Electromagnetic
Drive wheel type	Non-Marking Polyurethane
Castor wheel type	Non-Marking Polyurethane
Drive wheel diameter	250 mm
Point loading	0.49 (kg/mm ²) 4.80 [N/mm ²]
Drive motor power	1 kW
Controller type	AC
Standard machine speed (Without two speed selector switch)	2 KPH
Hare mode speed (With two speed selector switch)	3 KPH
Tortoise mode speed (With two speed selector switch)	1.2 KPH
Maximum slope	7°
Voltage	24 v
Noise level	Motor ≤80 dBA Flashing light ≤85 dBA Horn ≤112 dBA
Metal work finish	Stainless Steel 316 grade 240-grit abrasive to 0.6μ satin finish
IP rating	IP44 IP55†
Hydraulic Specification	
Maximum Lift Force at the Coupling	1,025 kg
Sealed Lead Acid Battery	
Product code	Z71-00300
Battery pack capacity	102 Ah
Maximum distance per charge*	12.4 km
Charge time (External charger)	8 hrs 15 mins
External Charger	
Product code	Z71-00402
Input voltage	85 - 265 v
Hertz	50 - 60 Hz
Amps	15 A
Phase (single, three)	Single
IP Rating	IP30

† The MT5/400+ SS is available with an increased IP55 ingress protection rating. Contact your representative for further details.

Technical Specification

Internal Charger	
Product code	Z71-00401
Input voltage	85 - 265 v
Hertz	50 - 60 Hz
Amps	15 A
Phase (single, three)	Single
IP rating	IP30
Lithium Battery	
Product code	Z71-00302
Battery pack capacity	117 Ah
Maximum distance per charge*	15 km
Charge time	3 hrs
Charging	
Product code	Z71-00403
Input voltage	85 - 265 v
Hertz	50 - 60 Hz
Amps	40 A
Phase (single, three)	Single
IP rating	IP30
Coupling	
CombiCoupling (male I female)	Optional
BoxCoupling (male I female)	Optional
Safety	
Key Switch	Standard
Emergency Stop	Standard
Battery Discharge Indicator	Standard
Anti-Crush Button	Standard
Warning Horn	Standard
Automatic Cut Off (as tiller arm returns to vertical)	Standard
Automatic Parking Brake	Standard
Options	
Additional Battery	Optional
Flashing Safety Light and Motion Bleeper	Optional
Two Speed Selector Switch	Optional
CombiLock	Optional
Stainless Steel Drive Wheel	Optional
Quick Release Coupling Pins	Optional

MasterMover®

mastermover.com

© Copyright 2023

UK
CA

CE

ISO 9001

ISO 45001